

# feature radiators

## DUOLINE

Price list with effect from 1<sup>st</sup> February 2012



### DUOLINE – single tubes

| model       | height (mm) | width (mm) | output watts / btu | white £ | Accessories  |                |
|-------------|-------------|------------|--------------------|---------|--------------|----------------|
|             |             |            |                    |         | Towel rail £ | Towel hooks* £ |
| DUO/100/036 | 1000        | 360        | 730 / 2491         | 268     | 10           | 10             |
| DUO/120/036 | 1200        | 360        | 851 / 2904         | 262     | 10           | 10             |
| DUO/150/022 | 1500        | 225        | 640 / 2184         | 183     | 10           | 10             |
| DUO/180/027 | 1800        | 270        | 905 / 3088         | 230     | 10           | 10             |

### DUOLINE – double tubes

| model       | height (mm) | width (mm) | output watts / btu | white £ | Accessories  |                |
|-------------|-------------|------------|--------------------|---------|--------------|----------------|
|             |             |            |                    |         | Towel rail £ | Towel hooks* £ |
| DUO/150/036 | 1500        | 360        | 1693 / 5777        | 459     | 10           | 10             |
| DUO/150/045 | 1500        | 450        | 2116 / 7220        | 541     | 10           | 10             |
| DUO/180/036 | 1800        | 360        | 1977 / 6746        | 492     | 10           | 10             |
| DUO/210/031 | 2100        | 315        | 1960 / 6688        | 471     | 10           | 10             |
| DUO/210/045 | 2100        | 450        | 2800 / 9554        | 656     | 10           | 10             |

Towel rails and hooks are not included as standard.

Towel rails are 600mm wide but can be cut down on site for narrower rail. \*Towel hooks are sold as a pair.

- White: all sizes usually in stock in the UK
- Tube diameter: 35mm
- Distance from wall to front face: duoline single - 105mm / duoline double - 124mm
- Side valve connections so add 150mm in total to the width of the radiator to allow for valves. (These are not pipe centres.)
- Floor supports available – only required where radiators are being attached to unusually weak walls, ask for details.
- Approximate pipe centres can be provided if you wish to install your pipework in advance of receiving your radiator. Radiators are supplied with the necessary fixings i.e. brackets, spacers, air vents etc (note: screws are not supplied).
- To complete the look, see our valves page (valves are not included as standard).
- Nationwide delivery available – usually £25 per consignment.
- To order or for further information, please call or email.
- Heat outputs are shown at operating temperatures of 90/70/20 ( $\Delta t 60^{\circ}\text{C}$ ).
- All sales are subject to our standard terms and conditions, a copy of which can be downloaded from our website.

**The above prices are exclusive of VAT.**

**[www.featureradiators.co.uk](http://www.featureradiators.co.uk)**

Bingley Railway Station, Wellington Street, Bingley, West Yorkshire BD16 2NB  
Tel. 01274 567789 Fax. 01274 561183 Email: [contact@featureradiators.co.uk](mailto:contact@featureradiators.co.uk)