

feature radiators

Effective from 1st February 2012



4 section dark olive brown shown above

BURLINGTON

Create the elegance of a bygone era
with this cast iron radiator.

Supplied pre-assembled up to 15 sections

BURLINGTON - 838mm high (214mm deep)

Sections	Width (mm)	Heat output		Dark olive brown (Semi gloss primer/top coat) £	Painted in other standard finishes £	#Painting surcharge (if applicable) £
		Watts	BTUs			
3	252	516	1760	347	377	[79]
4	328	689	2351	455	495	[69]
5	404	863	2945	564	614	[59]
6	480	1035	3531	672	732	[49]
7	556	1207	4118	780	850	[39]
8	632	1380	4709	887	967	[29]
9	708	1552	5295	995	1085	[19]
10	784	1724	5882	1104	1204	[9]
11	860	1892	6455	1212	1322	0
12	936	2069	7059	1320	1440	0
13	1012	2236	7628	1428	1558	0
14	1088	2408	8215	1536	1676	0
15	1164	2587	8827	1645	1795	0
16*	1240	2753	9388	1753	1913	0
17*	1316	2925	9974	1861	2031	0
18*	1392	3097	10561	1969	2149	0
19*	1468	3269	11153	2077	2267	0
20*	1544	3441	11739	2185	2385	0
21*	1620	3613	12326	2298	2508	0
22*	1696	3784	12912	2406	2626	0
23*	1772	3956	13499	2515	2745	0
24*	1848	4128	14086	2623	2863	0

Longer radiators available by special order, please ask for details.

*Radiators will arrive in 2 blocks to be joined together on site. Joining tool required and supplied on a sale or return basis (£100 + VAT refundable deposit)

#Painting surcharge does not apply if more than one radiator is ordered in the same colour.

IMPORTANT INFORMATION OVERLEAF

The above prices are exclusive of VAT.

www.featureradiators.co.uk

bingley railway station, wellington street, bingley, west yorkshire bd16 2nb
tel. 01274 567789 fax. 01274 561183 email: contact@featureradiators.co.uk

feature radiators

Finishes:

Primer:	For on site painting or for delivery direct to your chosen painting company in the UK
Standard painted finishes:	Traditional matt metallics - antique gold, light old penny, dark old penny, natural cast iron, anthracite, pewter – colour card available Wide range of semi-gloss RAL colours – colour card available
Bespoke colour match:	We can colour match to any non-textured paint range (including Farrow and Ball, Aga, Rayburn, Little Greene Paint Co, Fired Earth, Paint Library and Dulux colours) for an additional charge.

Notes:

Cast iron radiators have a textured finish. For a smooth finish please see our Classic and Bordo ranges, which are made of steel.

Shade variations may occur from one paint batch to the next and over the years our standard for some colours has changed. Accordingly, where radiators are to be used in the same room and/or a colour match is important, it is advisable to order all radiators at the same time. If you are looking to colour match to radiators ordered previously, please make us aware of this at time of order so we can minimize shade variation.

Pewter, white, cream and other light coloured paint finishes will highlight the imperfections characteristic of cast iron more than the darker colours.

For radiators in primer, we strongly advise against powder coating as this process can weaken the seals between sections. Powder coating will invalidate the manufacturer's guarantee.

IMPORTANT INFORMATION

- Lead times - dark olive brown (semi-gloss primer): allow 10 – 15 working days / other finishes: please allow 5 weeks.
- Our radiator sections are joined together using seals that have been specifically sourced to ensure a neat finish between sections. This avoids the risk of paint issues that have been seen in cast iron radiators where standard seals are used.
- Delivery - nationwide - usually £25 per consignment.
- Manufacturer's guarantee - 10 year manufacturer's guarantee against manufacturing defects – maximum working pressure of 6 bar.
- Ready assembled - up to 15 sections can be delivered to site ready assembled. * For larger sizes a joining tool is required.
- Other sizes available – shown above are the most popular sizes. Other sizes available. For longer sizes further sections may be assembled on site – each section is 76mm wide, end bushes = 24mm.
- Fixings - radiators are supplied with the necessary fixings i.e. wall bracket, plugs, bushes, vents, ½" connections as standard (¾" connections available on request) - note: screws are not supplied.
- Valves - to complete the look see our valves page for traditional style valves (valves are not included as standard).
- Heat outputs are shown at operating temperatures of 90/70/20 ($\Delta t 60^{\circ}\text{C}$).
- Pipe centre measurements
- Wall to pipe centre measurements: 125mm or 135mm - the standard bracket supplied has a choice of 2 settings. Use the greater wall to pipe centre measurement to accommodate skirting boards. Adjustable bracket available on request.
- Tapping centres = length of radiator.
- Pipe centre to pipe centre = tapping centres (width of radiator) *plus* appropriate amount for valves.
- Water treatment – the manufacturer's guarantee will only be valid if your radiators are installed in accordance BS 5449 section five commissioning. On completion of installation the system should be properly flushed and filled to remove debris and minimise the presence of solid particles and chemical residues, which may cause corrosion and damage within the system. Use of the corrosion inhibitor should be in accordance with the manufacturer's instructions and recommendations and should take into account the particular metals within the system.
- All sales are subject to our standard terms and conditions, a copy of which can be downloaded from our website.

The above prices are exclusive of VAT.

www.featureradiators.co.uk

bingley railway station, wellington street, bingley, west yorkshire bd16 2nb
tel. 01274 567789 fax. 01274 561183 email: contact@featureradiators.co.uk