

feature radiators

Effective from 1st February 2012



Clasico 2 Column, 20 sections, wall-mounted in white



Clasico 2 column, 10 sections, floor-mounted in green

Clasico 2 column

Two column cast iron radiator
Timeless and versatile
Floor-mounted or wall-mounted

Sits close to the wall, so ideal for smaller rooms or narrow corridors where space is at a premium.

Sizes listed below are supplied pre-assembled. Longer sizes also available for on site assembly.

Please specify floor or wall-mounted at time of ordering.

2 Column – floor standing (including feet)

63mm deep

Model	Sections	Height (inc. feet)	Width (mm)	Heat output		Primer £	Standard Paint Finish £	Standard paint surcharge (if applicable)# £
		(mm)		Watts	BTUs			
FLR-80/2/4	4	777	264	377	1287	154	194	[69]
FLR-80/2/5	5	777	324	472	1609	176	226	[59]
FLR-80/2/6	6	777	384	566	1931	202	262	[49]
FLR-80/2/7	7	777	444	660	2252	226	296	[39]
FLR-80/2/8	8	777	504	754	2574	250	330	[29]
FLR-80/2/9	9	777	564	849	2896	272	362	[19]
FLR-80/2/10	10	777	624	943	3218	296	396	[9]
FLR-80/2/11	11	777	684	1037	3539	320	430	0
FLR-80/2/12	12	777	744	1132	3861	344	464	0
FLR-80/2/13	13	777	804	1226	4183	369	499	0
FLR-80/2/14	14	777	864	1320	4505	393	533	0
FLR-80/2/15	15	777	924	1415	4826	415	565	0
FLR-80/2/16	16	777	984	1509	5148	439	599	0
FLR-80/2/17	17	777	1044	1603	5470	465	635	0

2 Column – wall mounted (without feet)

63mm deep

Model	Sections	Height	Width (mm)	Heat output		Primer £	Standard Paint Finish £	Standard paint surcharge (if applicable)# £
		(mm)		Watts	BTUs			
WALL-80/2/4	4	712	264	377	1287	154	194	[69]
WALL-80/2/5	5	712	324	472	1609	176	226	[59]
WALL-80/2/6	6	712	384	566	1931	202	262	[49]
WALL-80/2/7	7	712	444	660	2252	226	296	[39]
WALL-80/2/8	8	712	504	754	2574	250	330	[29]
WALL-80/2/9	9	712	564	849	2896	272	362	[19]
WALL-80/2/10	10	712	624	943	3218	296	396	[9]
WALL-80/2/11	11	712	684	1037	3539	320	430	0
WALL-80/2/12	12	712	744	1132	3861	344	464	0
WALL-80/2/13	13	712	804	1226	4183	369	499	0
WALL-80/2/14	14	712	864	1320	4505	393	533	0
WALL-80/2/15	15	712	924	1415	4826	415	565	0
WALL-80/2/16	16	712	984	1509	5148	439	599	0
WALL-80/2/17	17	712	1044	1603	5470	465	635	0

#Painting surcharge does not apply if more than one radiator is ordered in the same colour.

Important information detailed overleaf.

www.featureradiators.co.uk

Bingley Railway Station, Wellington Street, Bingley, West Yorkshire. BD16 2NB
Tel. 01274 567789 fax. 01274 561183 Email: contact@featureradiators.co.uk

feature radiators

Finishes

- Available in *matt metallic finishes* (antique gold, light old penny, dark old penny, natural cast iron, anthracite, pewter) and a selection of *semi-gloss finishes* (some RAL colours, gun metal and black). Colour cards available on request. We can also colour match to any non-textured paint range including Farrow and Ball, Aga, Rayburn, Little Greene Paint Co, Fired Earth, Paint Library, Dulux and Dulux Heritage colours for a surcharge.
- Shade variations may occur from one paint batch to the next and over the years our standard for some colours (including anthracite) has changed. Accordingly, where radiators are to be used in the same room and/or a colour match is important, it is advisable to order all radiators at the same time. If you are looking to match the colour of radiators ordered previously, please disclose this at the time of order, so we can do what we can to minimize the variation in shade.
- Warning: please be aware that pewter, white, cream and other light coloured paint finishes highlight the imperfections characteristic of cast iron more than the darker colours.
- Primer finish available for on site painting or we can deliver direct to your own painter in the UK. We strongly advise against powder coating this product as this process can weaken the seals between sections. Powder coating will invalidate the manufacturer's guarantee.
- These radiators have a textured finish that is characteristic of cast iron. If you are looking for a column style radiator with a smooth finish please see our Classic and Bordo ranges, which are made of steel.

- **Limited stock available.** All Clasico 2 column radiators are made to order. Lead times - Primer: please allow 10 – 15 working days / Top coat finish: please allow 5 weeks.
- Please note that orders for non-stock items (including those assembled to order, special colours/finishes and special sizes) cannot be cancelled.
- Our radiator sections are joined together using seals that have been specifically sourced to ensure a neat finish between sections. This avoids the risk of paint issues that have been seen in cast iron radiators where standard seals are used.
- Delivery - nationwide - usually £25 per consignment.
- 10 year manufacturer's guarantee against manufacturing defects – maximum working pressure of 6 bar.
- Ready assembled - up to 17 sections can be delivered to site ready assembled.
- Longer sizes - further sections may be assembled on site for longer radiators. Each section is 60mm. end bushes = 24mm. Joining tool with instructions can be supplied for £100 refundable deposit. Please ask for more details.
- Fixings - radiators are supplied with the necessary fixings i.e. wall brackets, plugs, bushes, vents, ½" connections as standard (¾" connections available on request) - note: screws are not supplied. Wall-mounted models are supplied with mounts and clamps. Floor-mounted models are supplied with mounts, clamps and feet.
- Distance from wall to front face - 100mm
- Valves - to complete the look see our valves page for traditional style valves (valves are not included as standard).
- Heat outputs are shown at operating temperatures of 90/70/20 ($\Delta t 60^{\circ}\text{C}$).
- **Pipe centre measurements**
 - Wall to pipe centre measurements:* 67mm or 77mm - the standard bracket supplied has a choice of 2 settings. Use the greater wall to pipe centre measurement to accommodate skirting boards. Adjustable bracket is available on request.
 - Tapping centres* = length of radiator
 - Pipe centre to pipe centre* = tapping centres (width of radiator) *plus* appropriate amount for valves.
- **Water treatment** – the manufacturer's guarantee will only be valid if your radiators are installed in accordance BS 5449 section five commissioning. On completion of installation the system should be properly flushed and filled to remove debris and minimise the presence of solid particles and chemical residues, which may cause corrosion and damage within the system. Use of the corrosion inhibitor should be in accordance with the manufacturer's instructions and recommendations and should take into account the particular metals within the system.
- All sales are subject to our standard terms and conditions, a copy of which can be downloaded from our website.

The above prices are exclusive of VAT.

www.featureradiators.co.uk

Bingley Railway Station, Wellington Street, Bingley, West Yorkshire. BD16 2NB
Tel. 01274 567789 fax. 01274 561183 Email: contact@featureradiators.co.uk